

"Splash" Pool Paint



"Splash" Pool Paint

DIRECTIONS & CONDITIONS for GOOD RESULTS PLEASE READ CAREFULLY

THE SURFACE to be painted MUST BE:-

- (a) **IN GOOD CONDITION.** Repaired if necessary and Solid.
- (b) **COMPLETELY FREE OF CONTAMINANTS** such as Body Grease, Sun Tan Lotion, Oil & Grease, Algae, Chemical Deposits, and those from Water Treatment, Calcium Carbonate, Water Based & Household Paints, Soft Chlor. Rubber Paints, etc. and also Completely Free of any traces of Products used to remove Contaminants.
- (c) **ROUGH ENOUGH** to enable good adhesion, say 60 grit. **EXCEPT**, Hard & fully attached Chlorinated Rubber, which when cleaned, is directly re-coatable with this product.
- (d) **GIVEN TIME TO DRY** completely, after Clean-up and Preparation. Up to 3 Dry days on many surfaces. (When Internal or Covered, Fan assistance to All Drying and Curing is usually necessary).
- (e) **FREE OF** any **DEW OR DAMPNESS**. Best ensured by **PAINTING IN THE LATE AFTERNOON** of a Dry day.
(About 8m² per litre per coat) **NOTE** - Do Not Paint, when the temperature is below 10 or above 30°C, or in windy conditions.
- (f) Have **TWO FULL STRENGTH COATS**. (24 hours or more apart) **NOTE** - Where the surface is Raw or Bare Concrete, Cement or Render e.g. Marble, a heavily thinned priming coat of this paint (using it's Special Thinner) is first applied.
- (g) Allowed **7 DAYS TO CURE** by **SOLVENT EVAPORATION**, before filling the Pool. To prevent Discolouration during this period, promptly remove any Ponding from Rain or Moisture.

For **FURTHER INFORMATION**, Please **CHECK** with your Supplier the type of surface Existing on Your Pool. (if necessary, by showing them a very small piece of the Surface or existing Paint) Please **ASK FOR** and obtain the Instruction Sheet to suit Your Pool, so as to achieve the Conditions shown in (a), (b), (c) and (d) above.

SAFETY - Wear appropriate Protection for Eyes and Skin. Do Not apply in confined area without using the proper Breathing Apparatus. Even in a Swimming Pool make sure there is sufficient air movement to remove chemical and solvent fumes.

Although the information and directions for use and application presented hereon are believed to be reliable, No Responsibility is accepted, or expressed or implied Warranty given, because performance of this product is affected by surface preparation and circumstances and application beyond our control. We recommend that Users conduct their own tests to establish suitability for their use. All the Statements in the Directions & Conditions hereon are the Property of International Traders Pty Ltd.

INTERNATIONAL TRADERS

PTY LTD-BRISBANE- A.B.N.27100193619

6/286 Evans Rd

Salisbury Q 4107

Fax: (07) 3272 9744

Phone: (07) 3272 9051

